Canon

Color imageCLASS MF8580Cdw/MF8280Cw

Revolutionizing Today's Workspace

Color Laser Multifunction Printers PRINT | COPY | SCAN | FAX

- Wireless Connectivity lets you print from almost anywhere in your home or office
- Print on the go with Canon Mobile Printing,*
 Apple[®] AirPrint[™], and Google Cloud Print[™]
- Easily access the scan, eco-copy, and secure print (MF8580Cdw only) functions right from the control panel with the **Simple Solution Keys**
- Seamlessly navigate through all the features with the 7-line color LCD display
- Print/Copy in both color and black and white at blazing speeds: Up to 21 ppm** (MF8580Cdw) Up to 14 ppm** (MF8280Cw)
- **Duplex Versatility** allows two-sided printing, copying, scanning, and PC faxing (MF8580Cdw only)
- Send scanned documents and forward received faxes to a recipient through e-mail or file server (MF8580Cdw only)
- Energy Saver mode uses only 2W of energy
- Single-Cartridge System for easy supply replenishment















Advanced technologies for your home and office



Print Documents On the Go Print a variety of file types, Web pages, and images on the go with the Canon Mobile Printing app.*



Wherever you are, print from your smartphone or computer using Google Cloud Print enabled apps.



The Color imageCLASS MF8580Cdw and MF8280Cw feature password-protected Department ID Management.

Device usage and color access can be monitored and controlled, which can help to reduce costs. With this feature, up to 300 IDs can be monitored.





Apple AirPrint allows you to print documents, e-mails, Web pages, and photos to your compatible imageCLASS devices from your iPhone®, iPad®, or iPod touch®.

Environmentally Conscious

Help reduce your power consumption with Canon's efficient Energy Saving Mode. The MF8000 Series uses just two watts of energy during Energy Saving mode and meets ENERGY STAR® Guidelines, helping you save money on energy costs.





Secure Print

The Color imageCLASS MF8580Cdw features Secure Print to help protect the privacy of your printed documents. To help ensure that your documents end up in the right hands, follow the simple steps below:

- 1. Enter code on PC.
- 2. Select the one-touch "Secure Print" button on the device.
- 3 Enter the code on the MF8580Cdw.
- 4. Pick up the secure print.



* Requires Canon Mobile Printing app available free on the App store. Compatible with iPhone 5, iPhone 4S, iPhone 4, iPad mini, iPad 4, the new iPad, iPad 2, and the original iPad running OS 6.0.1 - 6.1.2.

** Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper.

Generation Green

The MF8000 Series is part of Canon's Generation Green Program, which highlights the company's commitment to sustainability. Learn more at www.usa.canon.com/green.



Color LCD Display

The intuitive seven-line Color LCD Display allows users to navigate through the menu seamlessly. The wide screen and color display are easy to read, helping you to complete tasks in a breeze.



FEATURES	Color imageCLASS MF8580Cdw	Color imageCLASS MF8280Cw	
Functions	BASIC SPECIFIC Print/Copy/Scal		
Print Speeds	Print/Copy/Scan/Fax/PC Fax Up to 10 ppm* (2-sided, plain paper letter) Up to 14 ppm* (1-sided, plain paper letter)		
(default print mode: 2-sided)	Up to 21 ppm* (1-sided, plain paper letter)		
Connectivity	USB 2.0 Hi-Speed, 10/100 Base-T Ethernet, 802.11 b/g/n Wireless** Windows [®] 8, Windows 7, Windows Server [®] 2012, Windows Server 2008 R2, Windows Server 2008,		
Operating Systems	Windows Vista [®] , Windows Server 2003, Windows [®] XP, Mac [®] OS X 10.5.8 and up, Linux (print only)		
	(Drivers available for download		
_	Duplex Automatic Document Feeder: 50-sheet	Simplex Automatic Document Feeder: 50-sheet	
	Standard Cassette: 250-sheet;† 16-58 lb. Bond; Letter, Legal, A4, A5, B5, Statement, Executive	Standard Cassette: 150-sheet; † 16-58 lb. Bond; Letter, Legal, A4, A5, B5, Statement, Executive	
Paper Handling	Multipurpose Tray: 50-sheet; † 16-58 lb. Bond	Multipurpose Tray: 1-sheet; † 16-58 lb. Bond	
	Platen Size: U		
	ADF Size: 5" x 5.5" to 8.5" x 14" Output Tray: 125 Sheets (face-down)		
Duplex	All Mode (Print, Copy, Scan, Fax)	N/A	
Duty Cycle	Up to 40,000 Pages per Month	Up to 30,000 Pages per Month	
Security	IEEE802.1x, SNMPv3, HTTPS, IPsec, Secure Print,	IEEE802.1x, SNMPv3, HTTPS, IPsec,	
-	Department ID Management	Department ID Management	
First-Print Time	PRINTER SPECIFICATIONS Plack/Calaxy 14.2 coconde av loss (Lattav)tt Plack/Calaxy 14.2 coconde av loss (Lattav)ty Placky 14.2 coconde av loss (Lattav)ty Plac		
Printer Language	Black/Color: 14.3 seconds or less (Letter) ⁺⁺ UFR II LT (Host-based), PCL 6 (5e,XL)	Black/Color: 18 seconds or less (Letter) ⁺⁺ UFR II LT (Host-based)	
Print Resolution	1200 x 1200 dpi equivalent (240	· /	
Print Features	Print Modes (Watermark, Page Composer,	Print Modes (Watermark, Page Composer,	
	Toner Saver, Poster, Booklet)	Toner Saver, Poster)	
Print Memory Mobile Print	512MB (Shared with Copy Memory)	256MB (Shared with Copy Memory)	
Mobile Print	Ile Print Canon Mobile Printing,* Apple AirPrint, Google Cloud Print COPIER SPECIFICATIONS		
	Black: Approx. 15.3 Seconds ^{†††} (Letter)	Black/Color: Approx. 19 Seconds ⁺⁺⁺ (Letter)	
First Copy Time	Color: Approx. 16 Seconds+++ (Letter)		
Copy Resolution	Up to 600 x 600 dpi		
Halftones	256 Levels		
Max. Number of Copies Copy Features	99 Copies Reduction/Enlargement 25%-400%, Collate, 2 on 1, 4 on 1, ID Card Copy, Frame Erase, Copy Modes (Text/Photo/Map)		
copyreatures	SCANNER SPECIF		
Scan Type	Color Contact Image Sensor (CIS); 24-bit C		
Scan Speed	Black-and-white: 21 ipm ⁴		
•	Color: 10 ipm▲		
Scan Resolution Output File Formats	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 (interpolated) PDF (Compact), PDF, JPEG, TIFF		
Scan Features	Scan to USB, Push (Scan to PC) and Pull Scan,	Scan to USB, Push (Scan to PC) and Pull Scan	
	Scan to E-mail, Scan to Network Folder		
	FAX SPECIFIC/		
Modem Speed Fax Resolution	Up to 33.6 Kbps (Super G3)**		
Fax Memory	Up to 406 x 391 dpi (ultra fine) Up to 512 Sheets		
Speed Dialing	Up to 181 Dials (One-Touch plus Coded Dials)		
Group Dialing	199 Destinations		
Sequential Broadcasting	210 Destinations		
PC Fax	Yes (sendi		
Fax Forwarding	Yes (FaxgFax, E-mail, SMB)	Yes (FaxgFax)	
Fax Features	Fax/Telephone Auto Switch, Remote Reception, E Error Correction Mode, Auto Redial, Act		
	GENERAL SPECIF		
Dimensions	17"(W) x 19.1"(D) x 18.9"(H)	17"(W) x 19.1"(D) x 16.9"(H)	
Weight	63.1 lb. (w/o CRG); 68.3 lb. (w/ CRG)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG)	
	63.1 lb. (w/o CRG); 68.3 lb. (w/ CRG) Approx. 81.0 lb.	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb.	
Weight Package Weight	63.1 lb. (w/o CRG); 68.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS	
Weight	63.1 lb. (w/o CRG); 68.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh	
Weight Package Weight	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W	
Weight Package Weight Typical Energy Consumption (TEC)	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation:	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation:	
Weight Package Weight Typical Energy Consumption (TEC)	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure)	
Weight Package Weight Typical Energy Consumption (TEC) Power Consumption	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power)	
Weight Package Weight Typical Energy Consumption (TEC)	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power) 64.5dB or less in B/W (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power) 61.6dB or less in B/W (sound power)	
Weight Package Weight Typical Energy Consumption (TEC) Power Consumption	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power)	
Weight Package Weight Typical Energy Consumption (TEC) Power Consumption	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power) 64.5dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 36.5dB or less (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power) 61.6dB or less in B/W (sound power) 61.6dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 22.5dB or less (sound power)	
Weight Package Weight Typical Energy Consumption (TEC) Power Consumption	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power) 64.5dB or less in B/W (sound power) 64.5dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 36.5dB or less (sound power) 36.5dB or less (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power) 61.6dB or less in B/W (sound power) 61.6dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 22.5dB or less (sound power)	
Weight Package Weight Typical Energy Consumption (TEC) Power Consumption	63.1 lb. (w/o CRG); 58.3 lb. (w/ CRG) Approx. 81.0 lb. ENVIRONMENTAL SPI 0.9kWh During Operation: Approx. 450W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 50.3dB in Color (sound pressure) 50.9dB in B/W (sound pressure) 64.9dB or less in Color (sound power) 64.5dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 36.5dB or less (sound power)	52 lb. (w/o CRG); 57.3 lb. (w/ CRG) Approx. 67.2 lb. CIFICATIONS 0.4kWh During Operation: Approx. 400W Standby: Approx. 23W Energy Saver: Approx. 2W During Operation: 46.7dB in Color (sound pressure) 47.5dB in B/W (sound pressure) 61.3dB or less in Color (sound power) 61.6dB or less in B/W (sound power) 61.6dB or less in B/W (sound power) During Standby: Inaudible (sound pressure) 22.5dB or less (sound power)	

* Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper.

** Wireless performance may vary based on terrain and distance between the printer and wireless network clients. Requires Spenomiance may vary based on remain and distance between the primer and whereas network cherks.
 Requires Canon Mobile Printing app available free on the App store. Compatible with iPhone 5, iPhone 4S, iPhone 4, iPad mini, iPad 4, the new iPad, iPad 2, and the original iPad running OS 6.0.1 - 6.1.2.
 Based on 20 lb. Bond paper.
 May vary depending on the output environment.

tttLetter-sized, after being restored from Energy Saver mode.

▲Based on Letter-sized scanning at 300 x 300 dpi. ▲The Public Switched Telephone Network currently supports fax modem speeds of 28.8 Kbps or lower, depending on telephone line conditions. Sending and receiving fax machines need to conform to ITU-T v.34 guidelines. ▲▲▲ Based on ITU-T #1 Chart (standard mode).

--Declared noise emission in accordance with ISO 9296.



Color imageCLASS MF8580Cdw and Accessories

Color imageCLASS MF8580Cdw (120V)	6849B005AA
Color imageCLASS MF8580Cdw (230V)	6849B006AA
Cartridge 118 Black (yields approx. 3,400 pages based on ISO/IEC Standard)	2662B001AA
Cartridge 118 VP Black (yields approx. 6,800 pages based on ISO/IEC Standard)	2662B004AA
Cartridge 118 Yellow (yields approx. 2,900 pages based on ISO/IEC Standard)	2659B001AA
Cartridge 118 Magenta (yields approx. 2,900 pages based on ISO/IEC Standard)	2660B001AA
Cartridge 118 Cyan (yields approx. 2,900 pages based on ISO/IEC Standard)	2661B001AA
Cassette Feeding Unit-V1 (250-sheet Cassette)	0732A024AB

Color imageCLASS MF8280Cw and Accessories

Color imageCLASS MF8280Cw (120V)	6848B006AA
Cartridge 131 Black (yields approx. 1,400 pages based on ISO/IEC Standard)	6272B001AA
Cartridge 131 Black H (yields approx. 2,400 pages based on ISO/IEC Standard)	6273B001AA
Cartridge 131 Yellow (yields approx. 1,500 pages based on ISO/IEC Standard)	6269B001AA
Cartridge 131 Magenta (yields approx. 1,500 pages based on ISO/IEC Standard)	6270B001AA
Cartridge 131 Cyan (yields approx. 1,500 pages based on ISO/IEC Standard)	6271B001AA



www.cla.canon.com

Canon Latin America, Inc. 703 Waterford Way Suite 400 Miami, FL 33126



As an ENERGY STAR partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. CANON, IMAGECLASS, and SUPER G3 are registered trademarks of canon Inc. in the United States and may also be registered trademarks or there countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice. @2013 Canon U.S.A., Inc. All rights reserved.

0177W523